

# MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone: (800) 840-8420 • Web: [www.shopfox.biz](http://www.shopfox.biz)

## MODEL M1113 SHOP FOX® WOOD / METAL BANDSAW

### Product Dimensions

Weight..... 314 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 40 x 31 x 76 in.  
Footprint (Length x Width)..... 26-1/2 x 20 in.

### Shipping Dimensions

Type..... Wood Slat Crate  
Content..... Machine  
Weight..... 327 lbs.  
Length x Width x Height..... 19 x 33 x 79 in.

### Electrical

Power Requirement..... 220V, Single-Phase, 60 Hz  
Prewired Voltage..... 220V  
Full-Load Current Rating..... 5A  
Minimum Circuit Size..... 15A  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 16 AWG  
Plug Included..... No  
Recommended Plug Type..... 6-15  
Switch Type..... ON/OFF Push Button Switch w/Large Shut-Off Paddle  
Inverter Type..... Rhymebus RM5G-200V 1  
Inverter Size..... 1 HP

### Motors

#### Main

Type..... TEFC Induction  
Horsepower..... 1.5 HP  
Phase..... 3-Phase  
Amps..... 5A  
Speed..... 1725 RPM  
Power Transfer ..... V-Belt Drive  
Bearings..... Shielded & Permanently Lubricated

### Main Specifications

#### Operation Info

Blade Speeds..... 150 — 3000 (Variable) FPM  
Std. Blade Length..... 133 in.

## Cutting Capacities

Cutting Height.....	12 in.
Cutting Capacity Left of Blade.....	17-1/2 in.

## Construction

Table.....	Precision-Ground Cast Iron
Upper Wheel.....	Fully Balanced Aluminum
Lower Wheel.....	Fully Balanced Aluminum
Tire.....	Rubber
Body.....	Steel
Base.....	Steel
Wheel Cover.....	Steel
Paint Type/Finish.....	Powder Coated

## Other

Wheel Size.....	18 in.
-----------------	--------

## Table Info

Table Tilt - Left/Right.....	45 Right, 5 Left deg.
Table Size Length.....	24 in.
Table Size Width.....	18 in.
Table Size Thickness.....	1-3/4 in.
Floor To Cutting Area Height.....	37-1/4 in.

## Other

Country of Origin .....	Taiwan
Warranty .....	2 Years
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	ID Label on Center of Upper Wheel Cover
Sound Rating .....	74 dB
ISO 9001 Factory .....	No
CSA, ETL, or UL Certified/Listed .....	No

## Features

Precision-ground cast iron table  
Variable frequency drive speed control  
Left and right table tilting control  
Upper and lower blade guides  
Rack and pinion adjustment on upper blade guide support  
Fully balanced cast iron wheels w/rubber tires  
Quick release blade tension  
Steel guide blocks  
Two dust ports  
Wheel brush on lower wheel  
Blade tension scale with magnified cursor  
Twin drive belts  
Includes rip fence and miter gauge  
Rip fence comes with right and left reading indicators, T-slots, dead lift quick release